

SPECIFICATIONS OF GI FLEXIBLE HOSE CONDUIT

Material

Galvanized Steel

Properties

Good Flexibility

Light Weight

Excellent Bending Properties

Application Range

Machinery

Public utilities

Railway applications



ITEM NO.	G SYSTEM	OUTER DIAMETER (mm)	NATURAL CURVE (mm)	MAX. AXIAL PULL (Kgs)	STD PKG (m/ROLL)
MJS-6	3/16 "	8.2 ± 0.25	40	335	200
MJS-8	1/4 "	11.0 ± 0.30	45	470	200
MJS-10	5/16	13.5 ± 0.30	55	590	100
MJS-12	-	15.5 ± 0.35	60	710	100
MJS-13	3/8	16.5 ± 0.35	65	765	100
MJS-15	-	19.0 ± 0.35	80	885	100
MJS-16	1/2 "	20.0 ± 0.35	85	940	100
MJS-19	-	23.3 ± 0.40	95	1120	50
MJS-20	3/4"	24.3 ± 0.40	100	1180	50
MJS-25	1"	30.3 ± 0.45	120	1450	50
MJS-32	1 1/4 '	38.0 ± 0.50	150	1885	25
MJS-38	1 1/2 '	45.0 ± 0.60	180	2240	25
MJS-51	2 "	58.0 ± 1.00	220	3000	20
MJS-64	2 1/2 "	72.5 ± 1.50	310	3770	10
MJS-75	3 "	83.5 ± 2.00	350	4400	10
MJS-100	4 "	108.5 ± 3.0	410	4700	10